

Rinnai



Rinnai INFINITY® HD49 Series

Rinnai INFINITY® HD49 Features

- ✓ Appliance output of 28 L per minute (at a 25°C rise)
- ✓ Ability to reduce input to 199 MJ/h when closer flue clearances are required
- ✓ Maximum outlet temperature of 85°C
- ✓ Designed for easy servicing and replacement of key components
- ✓ Uses existing HD200 Series stainless steel flue system
- ✓ Inbuilt controller in indoor models, and status monitor in outdoor models

	INFINITY® HD49 Series			
REU Number	REU-VCM2837WC-ZK		REU-VCM2837FFC-ZK	
Order code	INFHD49L	INFHD49N	INFHD49FFL	INFHD49FFN
Install location	Outdoor	Outdoor	Indoor	Indoor
Gas Type	LPG	NG	LPG	NG
Thermal efficiency	83.5%	83.5%	83.5%	83.5%
Hot water capacity	1.4 - 37 L/min			
Hot water capacity (@ 25° C rise)	28 L/min			
Factory preset temperature	75°C	75°C	75°C	75°C
Max temperature	85°C	85°C	85°C	85°C
Gas Input	11 - 210 MJ/h			
Heat Output	48.8 kW			
Weight	20kg	20kg	21kg	21kg
Water - nominal operating pressure	220 - 1000 kPa			
Connection - hot	R3/4 (20mm)			
Connection - cold	R3/4 (20mm)			
Connection - gas	R3/4 (20mm)			
Ingress protection rating	IPX5	IPX5	IPX2	IPX2
Noise level (1m away)	52 dB(A)	52 dB(A)	54 dB(A)	54 dB(A)
Compliance - ES declaration number	DEC-000001841X8M7			
Power consumption				
Normal	95W	95W	66W	66W
Standby	2W	2W	2W	2W
Frost protection activation	120W	120W	104W	104W
Accessories				
Number of controllers	4	4	3	3
Order codes				
Recess box	R1407		N / A	
Pipe cover	R1417		R1417	

View the warranty conditions prior to purchase at rinnai.co.nz/warranty

Rinnai is constantly improving its products, and as such, information and specifications are subject to change without notice. For the most up-to-date information, go to rinnai.co.nz

This document has been printed using vegetable/soy-based inks on paper from environmentally responsible sources

Rinnai.co.nz | 0800 746 624

facebook.com/rinnainz