



<u>Standard Connection Sizes</u>			(E) Electrical	2 x 2kW - MS30055D020	2 x 8.7 Amps = 17.4 Amps	<u>Specifications</u>			
(A)	Cold	DN20 3/4" BSP		2 x 3kW - MS30055D030	2 x 13.0 Amps = 26.0 Amps	Water Pressure	TPR	850 kPa	Supplied
(B)	TPR	DN15 1/2" BSP		2 x 2kW - MS30055D20A	2 x 8.7 Amps = 17.4 Amps		PLV	500 kPa (approx.)	NOT SUPPLIED
(C)	Eco	DN15 1/2" BSP	<u>Construction</u>	2 x 3kW - MS30055D30A	2 x 13.0 Amps = 26.0 Amps		PRV (Cold Water)	700 kPa (approx.)	NOT SUPPLIED
(D)	Hot	DN20 3/4" BSP	Outer Tank			Weights (empty/full)		46.5 kg/ 346.5 kg	
			Inner Tank	Galvanised Steel					
			Insulation	2304 duplex stainless steel					
				High density expanded polyurethane foam					

Rinnai NZ Limited 105 Pavilion Drive Mangere, Auckland 2022	300L Mains pressure indoor stainless steel cylinders		Designed:	Spec #:
	2kW - MS30055D020		Drawn: KS	Date: 19/04/22
	3kW - MS30055D030		Scale @ A3: 20:1	Rev:
	2kW - MS30055D20A (ART)		Scale @ A4: 30:1	
	3kW - MS30055D30A (ART)			