

Mains pressure enamel indoor cylinder spares

This diagram is provided to assist you to identify parts if replacement is necessary. Contact your place of purchase or the manufacturer to enquire about parts, availability and/or service.



Cylinder	Element	Thermostat	TPR	Anode
30 L undersink	1.5 kW 30007 3.0 kW 30008	30014	30018	20117 (420 mm)
50 L undersink	1.5 kW 30007 3.0 kW 30008	30014	30018	20118 (500 mm)
135 L squat	3.0 kW 30001	30014	30018	20118 (500 mm)
180 L squat	2.0 kW 30000 3.0 kW 30001	30014	30018	20120 (1050 mm)
250 L	2.0 kW 30000 3.0 kW 30001	30014	30018	20122 (1440 mm)
300 L	2.0 kW 30000 3.0 kW 30001	30014	30018	20124 (1650 mm)

Additional comments

- 2 and 3 kW elements are curved dog-leg
- Thermostat is Robert Shaw black dial (MRT - manual reset thermostat)
- TPR is rated 850 kPa 10 kW 15 mm



Element replacement

Due to supply constraints some cylinders made in 2023 have different elements installed. To ensure ordering the correct replacement element, check if the cylinder has the below label. If it does, order the code shown on the label.

ELEMENT SPARE PARTS LIST	
PART NO	DESCRIPTION
30060	ENAMEL 2KW
30061	ENAMEL 3KW
30062	STAINLESS STEEL 2KW
30063	STAINLESS STEEL 3KW
(* includes element seal & backnut)	
Torque tighten backnut to 12Nm	

Element replacement for cylinders with this label

- 30060: Spare element kawai 2 kW
- 30061: Spare element kawai 3 kW



Elements have a temperature sensor pocket, element includes seal, backnut, and element key.

Note: As of June 2023, the element key is no longer included with the cylinder; it is now part of the element spare kit. DO NOT leave the element key inside the element enclosure due to potential electrical hazards.