
















Compact 2

ordering guide

1. Select gas type (engine)		
	Compact 2 NG engine	RIBF2N
	Compact 2 LPG engine	RIBF2L
Supplied with the engine is the ½ " BSPF male flare nut, adhesive back foam sealing strip, frame mounting screws (pre-installed into the engine mounting brackets), and the log set.		
2. Select frame option		
	Traditional black frame	R2524
	Black outer and stainless steel inner frame	R2525
	Stainless steel inner and outer frame	R2527
	Matt black steel frame	R2528
	Compact 2 black masonry infill panel (optional accessory to cover the gap behind the fire and frame)	R2329GL
3. Determine flueing option and select flue kits and/or flue components		
Masonry flueing		
	Compact flexiliner flue kit 3.6 m	R1758
	Flexiliner flue extension (for flues exceeding 3.6 m)	R1761
	Compact flexiliner flue spigot (refer note on previous page)	R1758-5F
	Stainless steel roof cowl	R1760-2
Mock chimney flueing		
	Compact inbuilt zero clearance box	R2520
	Zero clearance flue kit galvanised 3.6 m	R1762Z
	Zero clearance flue extension galvanised 1.2 m Zero clearance flue extension stainless steel 1.2 m	R1763Z R1763SS
	Wall penetration kit galvanised	R1766
	45 ° bend galvanised (contains; inner, outer, and spacer) two bends required per installation	R1764