



* Hidden by pipe cover

Standard Connection Sizes

- | | | |
|-----|------|-------------|
| (A) | Cold | DN20 ¼" BSP |
| (B) | Gas | DN20 ¼" BSP |
| (C) | Hot | DN20 ¼" BSP |

Electrical Normal - 58W

Standby - 2W (with 1 water control)
Standby with Anti-frost protection - 68W

Max output - 34.9kW

Specifications

- | | |
|--------------------------------|-------------------------------|
| Max Water Pressure | 1000kPa |
| Min Water Pressure | 160 kPa |
| Water Pressure Relief Valve | open- 2060kPa close- 1470 kPa |
| LPG and NG Max Gas Consumption | 156 MJ/h |
| Gas Pressure LPG | 2.75-3.0 kPa |
| Gas Pressure NG | 1.13-3.0 kPa |
| Gas Pressure Max | 3.5kPa |
| Noise level | 54dB(A) |
| Weight | 14kg |

For further information check - rinnai.co.nz

Rinnai NZ Limited
105 Pavilion Drive
Mangere, Auckland
2022

Rinnai Infinity with R1385 Pipe cover
INFA20L A20 External LPG
INFA20N A20 External NG

Designed:	Spec #:
Drawn: KS	Date: 24/05/22
Scale @ A4: 10:1	Rev: