



Standard Connection Sizes

(A)	Cold	DN20 3/4" BSP	
(B)	Gas	DN20 3/4" BSP	
(C)	Hot	DN20 3/4" BSP	
(D)	Electrical	A24: Normal - 56W Standby - 2W (with 1 water control) Standby with Anti-frost protection - 68W Max output - 42kW	A26: Normal - 66W Standby - 2W (with 1 water control) Standby with Anti-frost protection - 68W Max output - 44.5kW

Specifications

Max Water Pressure	1000kPa
Min Water Pressure	200 kPa
Water Pressure Relief Valve	open- 2060kPa close- 1470 kPa
LPG and NG Max Gas Consumption	A24: 184 MJ/h A26:199 MJ/h
Gas Pressure LPG	2.75-3.0 kPa
Gas Pressure NG	1.13-3.0 kPa
Gas Pressure Max	3.5kPa
Noise level	54dB(A)
Weight	15kg

For further information check - rinnai.co.nz

Rinnai NZ Limited
105 Pavilion Drive
Mangere, Auckland
2022

Rinnai Infinity
INFA24L A24 External LPG
INFA24N A24 External NG
INFA26L A26 External LPG
INFA26N A26 External NG

Designed:	Spec #:
Drawn: KS	Date: 24/05/22
Scale @ A4: 10:1	Rev: