

Rinnai



Rinnai INFINITY® HD56

Rinnai INFINITY® HD56 Features

- ✓ Appliance output of 32 L per minute (at a 25°C rise)
- ✓ Appliance input of 20.1 - 245 MJ/h for LPG, and 20.1 - 250 MJ/h for Natural Gas
- ✓ Maximum outlet temperature of 85°C
- ✓ Adjustable wall brackets to allow easy alignment of existing water, gas and flue connections
- ✓ Suitable to use as a solar boost for solar thermal installations

	INFINITY® HD56 Series	
REU Number	REU-AM3237WC-ZK	
Order code	INFHD56L	INFHD56N
Install location	Outdoor	Outdoor
Gas Type	LPG	NG
Thermal efficiency	82%	82%
Hot water capacity	1.5 - 3.7 L/min	
Hot water capacity (@ 25° C rise)	32 L/min	
Factory preset temperature	50°C	50°C
Max temperature	85°C	85°C
Gas Input	20.1 - 245 MJ/h	20.1 - 250 MJ/h
Heat Output	56.4 kW	56.8 kW
Weight	23 kg	23 kg
Water - nominal operating pressure	220 - 1000 kPa	
Connection - hot	R3/4 (20mm)	
Connection - cold	R3/4 (20mm)	
Connection - gas	R3/4 (20mm)	
Ingress protection rating	IPX5	IPX5
Noise level (1m away)	55 dB(A)	55 dB(A)
Compliance - ES declaration number	DEC-000002250L2L2	
Power consumption		
Normal	87 W	87 W
Standby	2 W	2 W
Frost protection activation	120 W	120 W

View the warranty conditions prior to purchase at rinnai.co.nz/warranty

Rinnai is constantly improving its products, and as such, information and specifications are subject to change without notice. For the most up-to-date information, go to rinnai.co.nz

This document has been printed using vegetable/soy-based inks on paper from environmentally responsible sources

Rinnai.co.nz | 0800 746 624

facebook.com/rinnainz