

Rinnai

Operation guide

Neo series



Gas fires, like cars, require regular maintenance and servicing. For reliable operation Rinnai gas fires should be serviced every two years, including inspection of the flue system.

Important

Appliance must be installed with a Rinnai approved flue system.

This appliance must be installed in accordance with:

- Manufacturer's installation instructions
- AS/NZS 5601 Gas Installations
- AS/NZS 5263 Gas appliances standards

For use with Natural Gas or Universal LPG as indicated on the appliance.

Appliance must be installed, commissioned and serviced by an authorised person, being in New Zealand a licensed gasfitter, in accordance with these instructions and all applicable local rules and regulations.

Warning

Improper installation, adjustment, alteration, service and maintenance can cause property damage, personal injury or loss of life.

For more information about buying, using, and servicing of Rinnai appliances call: 0800 RINNAI (0800 746 624).

Rinnai New Zealand Limited
105 Pavilion Drive, Mangere, Auckland
PO Box 53177, Auckland Airport, Auckland 2150

Phone: (09) 257-3800
Fax: (09) 257-3899
Email: info@rinnai.co.nz
Web: rinnai.co.nz
[youtube.com/rinnainz](https://www.youtube.com/rinnainz)
[facebook.com/rinnainz](https://www.facebook.com/rinnainz)

Contents


Safety.....	4
General information	5
About your Rinnai Neo	6
Operation using the remote	8
Operation using the Wi-Fi app	10
Clearances from combustibles.....	11
Mantels and surrounds.....	12
Abnormal flame pattern.....	13
Error codes.....	14
Troubleshooting.....	15
Installation checklist and installer details.....	17
Limited Warranty	18
Purchase details and product registration	back page

Safety


Important

This appliance is not intended for use by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of the appliance by a person responsible for their safety.


- The heater must not be used or operated if any part of the appliance is damaged
- Do not place articles on or against this appliance
- Do not use or store flammable materials near this appliance
- Do not spray aerosols in the vicinity of this appliance while it is in operation
- Do not modify this appliance
- The fire must not be located immediately below a power socket outlet (potential fire hazard)




Do not restrict warm air discharge by placing articles in front of the appliance.




This appliance must not be used for any other purpose other than heating.




Children should be supervised at all times to ensure they do not play with the appliance. Hand or body contact with the appliance should be avoided.




Do not allow anyone to sit, lean or sleep directly in front of the appliance.



Do not allow curtains or other combustible materials to come into contact with the appliance.




Do not unplug the appliance while it is operating. Do not use power boards or double adaptors to operate this appliance.



Do not allow anyone to post articles through into the heater.



Do not spray aerosols while the appliance is operating. Most contain butane gas which can be a fire hazard if used near the appliance.



If the supply cord is damaged it must be replaced by a licensed tradesperson. This must be a genuine replacement part available from Rinnai.

General information

Before operation please read these instructions to get an overview of how to operate, maintain and service your Rinnai gas fire.

Care and maintenance

All external surfaces of the fire can be cleaned using a soft damp cloth and mild detergent. Do not use solvents and do not attempt to clean the fire while it is hot or operating.

Electrical connection

The Neo is fitted with a 1.5 m power cord and 3-pin plug. The standard electrical connection is to the right hand side of the heater. If necessary this can be changed by your electrician to terminate on the left.

The connection is either direct wired* or connected to a power point within the cavity. This must be connected to a dedicated earthed power point. The electric isolation switch must be accessible after the appliance has been installed.

Installation by a licensed tradesperson

Only a licensed tradesperson can install, adjust, maintain, and service this gas fire. Any work carried out by a non-licensed tradesperson is illegal and will void any warranty.

Installer handover

Ensure your installer talks to you about the use and care of this appliance, and that you understand these instructions. The installer also needs to complete the appliance installation checklist and installer details, and leave this guide with you.

Safety devices

- **Overheat switches:** If the Neo gets too hot during operation, for example if the air outlet louvres get blocked, the overheat safety switches will turn off the gas and will only allow the fire to restart when it has cooled down.
- **Electrical fuse:** The electrical circuits are protected by a fuse.

- **Flame failure sensing system:** This device automatically cuts off the gas supply to the heater in the event the fire does not ignite after several attempts—this is to prevent gas building up inside the unit.
- **Power failure:** In the event of a power failure or power cut, the gas valves will automatically close and shut down the unit.

Soot deposits

Small soot deposits inside the heater or glass is normal. Significant soot build-up however is not normal and will require a service call. Refer to the troubleshooting section for further information.

Environmental

The Neo is manufactured from a number of recyclable materials. At the end of its useful life please consider what parts could be recycled, for example scrap metal, PCB etc.

Servicing

Rinnai has a maintenance, service and spare parts network with personnel who are fully trained and equipped to give the best advice on your Rinnai appliance.



Servicing and repair should only be carried out by authorised personnel, please call Rinnai (0800 746 624).

For reliable operation Rinnai gas fireplaces should be serviced every two years, including inspection of the flue system. If they are in a particularly dusty environment or subject to excess lint, for example dog hair, or where there are newly laid carpets, then annual servicing would be beneficial.

Regular maintenance and servicing is not covered by the Rinnai warranty.

* Consult a qualified electrician if direct wiring is required as it must comply with AS/NZS 5601 and AS/NZS 3000 and other relevant local regulations

About your Rinnai Neo

Congratulations on the purchase of your Rinnai Neo gas fireplace. The Neo range combines modern good looks with the latest advances in technology.

Interchangeable frames

Mix and match from a range of framing options. These can be interchanged at any time.



Control options

Infra-red and Wi-Fi control

Glass dress guard

Creates protection without obstructing the view.

Error display window

Sits on the top fold of the outer frame along with the filters.

Infra-red remote receiver window and ignition indicator

Will beep when it receives a signal from the remote and flash green during the ignition process.

Manual control panel on the side of the unit

The control panel is located on the top left corner of the outer frame. The control panel houses the ON/OFF button and also the LED indicator. This lets you know what the unit is doing. For example:

- Standby = LED is red
- Power disruption = LED flashes red



Infra-red simple remote or Wi-Fi control

Use the simple remote for basic control options or utilise the fully functional Wi-Fi app that allows for thermostatic control, and timer operation.

- Infra-red remote
The remote emits an infra-red signal. It must be aimed at the receiver window. Normal operating range is up to 7 m. Please note; range can be affected by the angle at which you are aiming the remote. Some fluorescent lights may interfere with the transmission of the remote signal—change your operating position if this occurs.
- Rinnai Wi-Fi app
Available from the Apple App store (iPhone) or Google Play (android devices), refer p. 10.

How the Rinnai Neo starts

By pressing the power button 'On' the fire will start the ignition sequence.

Ignition sequence:


1. When the On/Off button is pressed on the control panel, the infra-red receiver window will pulse green.
2. The ignition sparker will operate, and as soon as a spark is sensed gas will flow to the main burner.
3. When the main burner establishes a flame, the heater will automatically modulate between the burner settings to achieve and maintain the default set temperature of 22 °C¹.

Do not unplug or turn off the mains power supply to the fire as this will stop the convection fan from cooling down the unit. The convection fan operates for several minutes after the fire has been turned off.

Power cut or power disruption

If power is disrupted while the Neo is operating, once the power has been restored, the fire will go into power failure mode, the LED indicator will flash red, there will be flashing zeros in the error display window², and if using the app 00 (mains power failure) will appear on your smart device.

To reset the fire, press the ON/OFF button on the control panel, remote control, or on the app twice to turn the fire back on.



Position of your Rinnai Neo inbuilt on a wall

The Neo Inbuilt looks and performs best when installed close to the floor. If the unit is installed higher up the wall the movement of air from the convection fan, depending on the room configuration, could create draughts.

Wall surface above the fire

The temperature of the wall surface directly above the appliance may get warm and discolour paint finishes or distort vinyl wall coverings. For durability of surfaces, please contact the manufacturer for their specification. The finish needs to be able to withstand temperatures of up to 65 °C above ambient.

¹ On initial start-up (no additional buttons pressed), the Neo modulates the flame and heat output to try and maintain the default temperature setting of 22 °C. If the room temperature starts to climb above 22 °C the Neo will modulate to its lowest flame and fan setting, but will not turn off. Depending on the size of the room this could mean the room temperature could steadily rise.

² Error display window can be located in the lower left hand side of the frame, refer image on p. 14. The error will show through two narrow cutouts—you will need to walk up to the fire and look down to see these.

Operation using the remote

For the remote control functions to be available, the appliance On/Off button must be in the On position.

Signal transmission to the unit

The unit will beep and flash to confirm the settings have been received from the remote.

Lost or misplaced remote

If you misplace the remote the fire can still be used, albeit in a limited capacity, by using the power On/Off button on the top left hand corner of the outer frame. The fire will automatically modulate between flame settings to maintain the default set temperature of 22 °C.

Remote - safety



WARNING


Keep the remote away from young children. Also ensure they can't access the batteries—they can become a choke hazard and potentially life-threatening if swallowed.

Breakage of the plastic housing could expose sharp edges—replace the remote if this occurs.

Avoid getting the remote wet as water entry will damage the remote.

Batteries

The remote uses two Lithium cell CR2450 batteries. Never mix old and new batteries. The remote will be supplied with the batteries already inserted, pull the clear tab to activate (OH, meaning OK, will flash on the display). This will also occur when the batteries have been replaced.




Remove the batteries if the remote is not going to be used for a long time. This will help avoid damage from leaking batteries. If leakage has occurred the remote will need to be replaced as leaking chemicals could be a risk if touched or ingested.

Changing the batteries

• Remove the back


Slide your fingernail under the bottom corner and along the base, and gently pry apart. With some coaxing the cover will pop off. Patience required, remember it's designed so little fingers cannot easily access the batteries.



Remove back cover by prising apart from the bottom first

• Unscrew the black retaining bridge

Undo the two small screws holding the black retaining bridge between the two batteries.



• Replace the batteries

The batteries can only be inserted one way—printed side facing up as shown on the next page. The battery contact edges can be sharp, take care when replacing the batteries.

• Replace the black bridging plate

Ensure you replace the black bridging plate as this will reduce the risk of young children getting access to the cell batteries.

Flame and heat setting

Once the fire is turned on the flame setting defaults to level five (on high). Use the up and down buttons to control the height of the flame and heat output.

The relationship between the flame height and fan speed is preset and cannot be adjusted. The Neo has five flame and fan settings:

Flame height	Fan speed
1	low
2	low
3	low
4	high
5	high



Turning on and off

This button switches the fire on and off. For it to work the power button on the fire must be ON.

Indicative room temperature display

Displays the room temperature* (at the point of the remote) and low battery symbol if the batteries need changing. 

The back light will stay on for approximately five seconds. Constant activation will shorten battery life.

* Checks the room temperature every minute.

N.B: Do not compare the temperature readings from the remote and the app. The readings are being taken from different places and could vary significantly.

Black retaining bridge

Safety device that needs to be removed before replacing the batteries—DO NOT DISCARD, this MUST BE put back on.



Pry point for removing the back cover

Gently pry open the back cover from the base of the remote



Battery retainer

Temperature sensor position

The room temperature is determined by a temperature sensor located in the bottom of the remote. Please be aware the sensor will be affected by direct sunlight, draughts, and body temperature (your hand).

Operation using the Wi-Fi app

For the Wi-Fi app to work on your fireplace, you will need to have downloaded the app from the Apple App store or Google Play. The phone will then be paired to the fireplace and then to your home Wi-Fi connection.

Wi-Fi app features

The Rinnai fireplace app will quickly and easily enable you to perform a number of different functions via your mobile device.

- **Turn on the thermostat function**
Set a comfortable temperature and let the fire do the rest.
- **Switch to flame function**
An override of the thermostat function that allows a full-flame picture regardless of the room temperature.
- **Turn on timers**
For those that love ultimate control, multiple timers can be set and changed for every day of the week.



For more information about how to use the Rinnai Wi-Fi app, refer to the 'Wi-Fi control user guide' available on the Rinnai website, www.rinnai.co.nz, enter Wi-Fi user guide in the search field.

Clearances from combustibles

The clearances listed below, measured from the **edge of the inner glass**, are minimum clearances unless otherwise stated.

While the heater is operating

The appliance must not be installed where curtains or other combustible materials could come into contact with the heater. The 400 mm side clearance includes side walls.

Floor protection

Heat from this fire may over time affect the appearance of some materials used for flooring, such as, carpet, vinyl, cork or timber. This may be amplified if the air contains cooking vapours or cigarette smoke. To avoid this occurring, it is recommended that a mat be placed in front of this appliance.

Hearths


A hearth is not necessary, but can be used for decorative purposes or protection of sensitive flooring. A hearth, if installed, must not obscure the front of the fire.

TV installation above the fireplace

The Neo has a fan that distributes warm air from the top of the appliance out into the room. As warm air is dispersed outwards, as opposed to directly upwards, installation of a TV may be an option.

Generally the bottom of the television recess should be at least 400 mm above the fire. Please check with the television supplier to check clearances. Some television manufacturers have warranty conditions that state a television is not to be installed above a fireplace.

For further information, please contact Rinnai or refer to the installation manual. This illustrates recommended minimum clearances when installing a TV directly above the unit.



Neo Inbuilt clearances




Neo Freestanding clearances

Mantels and surrounds - inbuilt models only

Combustible mantels and surrounds require clearance from the unit to minimise the risk of fire. Mantels and surrounds, made of combustible materials such as wood, are allowed providing they are outside the minimum clearances shown.

The Neo gas fireplace is not designed to be built into bookcases.



A Mantel needs to be a minimum of 400 mm away from the edge of the inner glass.

B Maximum mantel depth at 400 mm (A) is 250 mm.

C Surround needs to be a minimum of 400 mm away from the edge of the inner glass.

For every 50 mm of added mantel depth there must be an additional 100 mm of clearance from the edge of the inner glass.

For example:

MANTEL DEPTH	A: CLEARANCE REQUIRED
300 mm	500 mm
350 mm	600 mm
400 mm	700 mm

Abnormal flame pattern


Each Rinnai Flame Fire has a distinct flame pattern. This should look the same every time you start your fire, after an initial warm up period of approximately 20 minutes.

Abnormal flame performance and/or pattern can indicate a problem with your fire, such as blocked gas injectors, or shifting of burn media.


There are some warning signs that could indicate a problem.

- Unusual smell from the appliance
- Continued difficulty or delay in establishing a flame
- Either very short or very long flames
- Flame only burns part way across the burner
- Severe soot building up on the inside of the glass¹


If any of the above signs occur, please contact Rinnai.



Normal flame pattern



Abnormal flame pattern



Soot build up

¹ Appliances incorporating a live fuel effect, and designed to operate with luminous flames, may exhibit slight carbon deposits—this is normal.

Error codes

The Neo has self diagnostic electronics that monitor the appliance during start up and operation. Should a fault occur the heater will shut down. The fault that has caused the shut down will be indicated by a pair of flashing numbers in the error display window in the lower left hand side of the frame. The error will show through two narrow cutouts—you will need to walk up to the fire and look down to see these.

Error code	Likely cause	Suggested solution
00	Mains power failure	Reset the fire, press the On/Off button on the control panel or remote control twice to turn the fire back on.
11	Ignition failure	Check the gas supply is turned on. Turn the heater OFF then ON again. If the problem continues a service call will be required.
12	Incomplete combustion	As above.
14	Overheat safety device	Service call.
15	Room overheat	Lower room temperature to below 40 °C.
31	Room temperature sensor faulty	Service call.
32	Overheat temperature sensor faulty	Service call.
33	Overheat temperature sensor faulty	Service call.
53	Spark sensor faulty	Service call.
61	Combustion fan motor faulty	Service call.
70	Model error	Incorrect PCB for model, service call.
71	Solenoids faulty	Service call.
72	Flame detection circuit fault	Service call.
73	Communication error	Service call.
90	Communication error detected between the main PCB and Wi-Fi module	Wi-Fi module in the fire needs resetting, service call.
91	Communication error detected between Smart device and Wi-Fi module	Please check your Wi-Fi and Rinnai Wi-Fi module are within range. Check network settings.

Neo - top view of frame, looking down



Error codes will show through these slots in the frame

Infra-red remote receiver window and ignition indicator

Troubleshooting

Uh-oh!

Check the following information before making a service call as some performance characteristics of the Neo are a normal part of operation. If you are still unsure or concerned after reading this section, please contact Rinnai.

During installation there will be an initial burning in period where some smoke and smell may be experienced. This is a normal part of the operation.

The appliance is fitted with an overheat safety switch which will shut off the appliance. If the appliance shuts off repeatedly servicing may be required.

Using the heater for the first time, or after a long period of non use

Ignition may not occur the first time it is operated due to air in the gas pipes. If ignition does not occur the unit will switch off automatically. Try operating the heater again if this occurs.

The heater may make noises after ignition or switching off. This is due to the expansion and contraction of the internal components—this is normal. The heater will not ignite if the On/Off button is pressed straight after the heater has turned off. It will take approximately 20 seconds before the unit will switch on again.

What's happening	Explanation and/or possible solution
Unusual smells	
Smoke or strange smells are produced when first operating the appliance after installation.	This is caused by grease, oil, or dust within the appliance. This will stop after a short time.
Smell of gas	Have you been painting? Have new carpets been laid? Have you been cooking with spices? If yes to any of the above, then this is normal as these odours will mix with the warm air to emit an unusual smell—this will dissipate over time. There could be a leak. Turn off the gas at the meter or LPG cylinder and call your installer.
Unusual sounds	
Clicking noises when the heater starts or stops, or changes to a higher or lower setting.	This is expansion and contraction of the heat exchanger and is a normal part of operation.
Clunking noise when the thermostat operates.	This is the sound of the gas valve opening and closing to regulate the flow of gas.
Soot marks and condensation on the glass	
Small soot deposit on logs or stones.	Normal operation, no action required.
Severe soot deposits forming on logs, stones, or glass	Inadequate flue system, incorrect gas pressure or incorrect installation of burn media. Contact a Rinnai Service Centre.
Condensation and/or water marks on the glass	Normal operation. Condensation should disappear once the fire has warmed up.

What's happening	Explanation and/or possible solution
Performance problems	
Warm air not coming from heater when it starts	The fan starts automatically after a short delay. This is to allow the appliance to warm up, helping avoid cold draughts.
Fan continues to run after the heater is turned off.	This is to remove residual heat from within the appliance. This stops once the unit cools down.
Fire will not light when switched on	Ensure the power cord is plugged in and turned on. Ensure gas supply is turned on.
Unit stops during operation	Possible power failure, or gas supply may have been turned off.
Remote problems	
Remote control doesn't work	Unit not plugged in properly or has been turned off—plug in power cord or press On/Off button. Remote lock-up due to signal being out of range, incorrectly aimed at unit or obstructed.
No display on remote.	Batteries may be flat, change batteries.
Possible error codes* on remote when batteries are activated or changed:	
F1 displays on remote	Assembly fault, remote will not respond to movement—accelerometer not communicating with the main processor correctly. Contact Rinnai.
F2 displays on remote	Room temperature outside 5-45 °C, or temperature sensing circuit has failed, which may indicate an assembly fault. Contact Rinnai.

* Unlikely to occur, but possible if there has been an assembly fault or failure with the remote.

Installation checklist

The installer must complete the installation and commissioning checklist below and leave this guide with you. They must also instruct you in the use and care of the Neo, and make sure you understand the safety instructions and operation of the appliance.



The glass dress guard fitted to this appliance reduces the risk of fire and injury and no part of it should be permanently removed.

Checklist

- Appliance positioned in a suitable location (clearances, mantels and surrounds etc.).
- Rinnai flue system installed and tested to ensure effective draw.
- Gas pressures checked and set.
- Burn media installed as per instructions.
- Glass dress guard fitted and customer advised not to remove.
- Appliance tested for correct operation and to ensure no gas leaks.
- Customer instructed on operating procedure and safety requirements.
- Customer advised to service the heater every two years.

Installer details

Company name:

Installer name:

Address:

Phone:

Mobile:

Certificate of compliance number for installation:

Signed:

Date:

Limited Warranty

Rinnai brings you peace of mind with a:

5-year firebox warranty



This warranty is applicable to all Rinnai gas fires manufactured from 01 April 2019. All terms of the warranty, subject to the conditions below, are effective from the date of first installation. The attending service person reserves the right to verify this by requesting a copy of the certificate of compliance prior to commencement of any warranty work. Proof of purchase and installation date will be required at the time of any warranty claim. This warranty is only valid within the country of purchase.

FIREBOX*		ALL OTHER PARTS	
Parts	Labour	Parts	Labour
5 years	2 years	2 years	2 years

* The firebox is the metal outer casing that surrounds the fire. All other parts of the fire will be covered by a two year limited warranty.

General warranty terms

All Rinnai appliances meet or exceed the safety standards required by New Zealand gas and electrical regulations. The company is constantly improving its products and as such, specifications are subject to change or variation without notice.

For the purposes of the Consumer Guarantees Act 1993, Rinnai only guarantees the availability of repair facilities and spare parts for the express warranty period recorded in the 'Warranty Summary' table above.

This warranty does not limit any consumer rights or guarantees that may apply under the Consumer Guarantees Act 1993. If the product is acquired for the purposes of a business, the provisions of the Consumer Guarantees Act 1993 do not apply and no other warranties (either express or implied by law) apart from those stated in the warranty will apply.

Warranty terms and conditions

1. All terms of this warranty are effective from the date of first installation. The attending service person reserves the right to verify this by requesting a copy of the certificate of compliance prior to commencement of any warranty work. The installer must issue a certificate of compliance by law in New Zealand. Warranty claims may be invalid if not accompanied by details of the installing or supervising gas fitter's registration number and the gas certification number.
2. All Rinnai appliances must be installed, commissioned, serviced, repaired and removed in accordance with the manufacturer's installation instructions, local regulations, and municipal building codes by persons authorised by local regulations to do so.
3. All appliances must be operated and maintained in accordance with the manufacturer's operating instructions. Rinnai recommends that gas appliances are serviced as per our service schedule.

Warranty terms and conditions continued

4. Servicing of the product is to be carried out by a Rinnai authorised service centre.
5. The warranty applies only to the components supplied by Rinnai. It does not apply to components supplied by others, such as electrical switches, electrical cables, fuses and where applicable flue systems but is not limited to these.
6. Where a failed component is replaced under warranty, the balance of the original appliance warranty will remain effective.
7. Rinnai reserves the right to transfer functional components from defective appliances if they are suitable.
8. Rinnai reserves the right to have installed product returned to the factory for inspection.
9. Where the gas fire is installed outside the metropolitan area or further than 40km from a Rinnai authorised service centre, travel costs shall be the owner's responsibility.

Warranty exclusions

The following exclusions may cause the warranty to become void and will result in a service charge and cost of parts (if required).

1. Accidental damage and acts of God.
2. Failure due to abuse or misuse, improper maintenance or improper storage.
3. Failure due to incorrect or unauthorised installations including but not limited to the use of products, including flue systems that are not specified by Rinnai, damage caused by installation of indoor fires outdoors and outdoor fires indoors.
4. Failure or damage caused by alterations, service or repair work carried out by persons other than Rinnai service persons or service centres.
5. Where it is found that there is no fault with the appliance and the issue is related to the installation or is due to the failure of electric or gas supplies.
6. Noise caused by minor contraction, movement or expansion of certain parts.
7. Cost of building work to access parts that need repair or replacement, or the costs of building repairs afterwards.
8. Subjective issues such as noise or smell that Rinnai have investigated (or a Rinnai service agent has investigated) and are established to be within normal operating parameters.
9. Variances in fireplace appearance from Rinnai promotional images that are due to gas type and printing confines.

Purchase details

Record your purchase details below

ATTACH YOUR PROOF OF
PURCHASE HERE:

Retailer:

Retailer address:

Date of purchase:

Product details:

Please keep these details in a safe place for future reference.

Register your Neo online

Register your Neo online at www.rinnai.co.nz/register/. You'll need to know the model, and also the serial number—shown on the sticker below.

To make a warranty claim, contact Rinnai on 0800 RINNAI (0800 746 624) or email info@rinnai.co.nz.



Experience our innovation

Rinnai.co.nz | **0800 746 624**

<http://www.youtube.com/rinnainz>

<http://www.facebook.com/rinnainz>