



Standard Connection Sizes

- (A) Cold DN20 3/4" BSP
- (B) Gas DN20 3/4" BSP
- (C) Hot DN20 3/4" BSP
- (D) Electrical LPG : Normal - 85W
 Standby - 2.4W (with 1 water control)
 Standby with Anti-frost protection - 150W
 Max output - 55.5kW

- NG : Normal - 70W
 Standby - 2.4W (with 1 water control)
 Standby with Anti-frost protection - 150W
 Max output - 55.5kW

Specifications

Max Water Pressure	1000kPa
Min Water Pressure	300 kPa
Water Pressure Relief Valve	open- 2060kPa close- 1470 kPa
LPG and NG Max Gas Consumption	209 MJ/h
Gas Pressure LPG	2.75-3.0 kPa
Gas Pressure NG	1.13-3.0 kPa
Gas Pressure Max	3.5kPa
Noise level	49dB(A)
Weight	29kg

For further information check - rinnai.co.nz

Rinnai NZ Limited 105 Pavilion Drive Mangere, Auckland 2022	Rinnai Infinity	
	INFN56FFL	N56 Internal commercial or domestic LPG
	INFN56FFN	N56 Internal commercial or domestic NG

Designed:	Spec #:
Drawn: KS	Date: 5/05/22
Scale @ A4: 10:1	Rev: