



* Hidden by pipe cover

Standard Connection Sizes

(A)	Cold	DN20 3/4" BSP	
(B)	Gas	DN20 3/4" BSP	
(C)	Hot	DN20 3/4" BSP	
(D)	Electrical	A24: Normal - 56W	A26: Normal - 66W
		Standby - 2W (with 1 water control)	Standby - 2W (with 1 water control)
		Standby with Anti-frost protection - 68W	Standby with Anti-frost protection - 68W
		Max output - 42kW	Max output - 44.5kW

Specifications

Max Water Pressure	1000kPa
Min Water Pressure	200 kPa
Water Pressure Relief Valve	open- 2060kPa close- 1470 kPa
LPG and NG Max Gas Consumption	A24: 184 MJ/h A26:199 MJ/h
Gas Pressure LPG	2.75-3.0 kPa
Gas Pressure NG	1.13-3.0 kPa
Gas Pressure Max	3.5kPa
Noise level	54dB(A)
Weight	15kg

For further information check - rinnai.co.nz

Rinnai NZ Limited
105 Pavilion Drive
Mangere, Auckland
2022

Rinnai Infinity with R1385 Pipe cover
INFA24L A24 External LPG
INFA24N A24 External NG
INFA26L A26 External LPG
INFA26N A26 External NG

Designed:	Spec #:
Drawn: KS	Date: 24/05/22
Scale @ A4: 10:1	Rev: