



Standard Connection Sizes

|     |      |      |        |
|-----|------|------|--------|
| (A) | Cold | DN20 | ¾" BSP |
| (B) | TPR  | DN15 | ½" BSP |
| (C) | Eco  | DN15 | ½" BSP |
| (D) | Hot  | DN20 | ¾" BSP |

|     |                     |                   |   |
|-----|---------------------|-------------------|---|
| (E) | Electrical          | 2kW - MS30055020  | 8.7 Amps                                |
|     |                     | 3kW - MS30055030  | 13.0 Amps                               |
|     |                     | 2kW - MS30055020A | 8.7 Amps                                |
|     |                     | 3kW - MS30055030A | 13.0 Amps                               |
|     | <u>Construction</u> | Outer Tank        | Galvanised Steel                        |
|     |                     | Inner Tank        | 2304 duplex stainless steel             |
|     |                     | Insulation        | High density expanded polyurethane foam |

Specifications

|                      |                  |                   |              |
|----------------------|------------------|-------------------|--------------|
| Water Pressure       | TPR              | 850 kPa           | Supplied     |
|                      | PLV              | 500 kPa (approx.) | NOT SUPPLIED |
|                      | PRV (Cold Water) | 700 kPa (approx.) | NOT SUPPLIED |
| Weights (empty/full) |                  | 46.5 kg/ 346.5 kg |              |

Rinnai NZ Limited  
 105 Pavilion Drive  
 Mangere, Auckland  
 2022

300L Mains pressure indoor stainless steel cylinders

- 2kW - MS30055020
- 3kW - MS30055030
- 2kW - MS30055020A (ART)
- 3kW - MS30055030A (ART)

|                  |                |
|------------------|----------------|
| Designed:        | Spec #:        |
| Drawn: KS        | Date: 19/04/22 |
| Scale @ A3: 20:1 | Rev:           |
| Scale @ A4: 30:1 |                |