



Standard Connection Sizes

(A)	Cold	DN20	¾" BSP
(B)	TPR	DN15	½" BSP
(C)	Eco	DN15	½" BSP
(D)	Hot	DN20	¾" BSP

(E) Electrical

2kW - MS18055020	8.7 Amps
3kW - MS18055030	13.0 Amps
2kW - MS18055020A	8.7 Amps
3kW - MS18055030A	13.0 Amps

Construction

Outer Tank	Galvanised Steel
Inner Tank	2304 duplex stainless steel
Insulation	High density expanded polyurethane foam

Specifications

Water Pressure	TPR	850 kPa	Supplied
	PLV	500 kPa (approx.)	NOT SUPPLIED
	PRV (Cold Water)	700 kPa (approx.)	NOT SUPPLIED

Weights (empty/full) 31.5 kg/ 211.5 kg

Rinnai NZ Limited
105 Pavilion Drive
Mangere, Auckland
2022

180L Mains pressure indoor stainless steel cylinders

2kW - MS18055020
3kW - MS18055030
2kW - MS18055020A (ART)
3kW - MS18055030A (ART)

Designed:	Spec #:
Drawn: KS	Date: 19/04/22
Scale @ A3: 20:1	Rev:
Scale @ A4: 30:1	