



Standard Connection Sizes				Specifications				Construction		
			Outer							
A	Cold inlet	DN50	2" BSP female		Water Pressure	TPR	1000 kPa	46kW 20mm supplied	Outer Tank	Coloursteel
B	Cold inlet	DN20	$\frac{3}{4}$ " BSP female			PLV	700 kPa (approx.)	NOT SUPPLIED	Inner Tank	Enamel Steel
C	Sensor pocket	DN20	$\frac{3}{4}$ " BSP female	6.5 mm i.d.		PRV (Cold Water)	850 kPa (approx.)	NOT SUPPLIED	Insulation	51mm of polyurethane-injected foam
D	Heat source return	DN50	2" BSP female	Max 75°C	Controlled heating source supply temp.		maximum 75°C		Anodes	2 x 25mm
E	Heat source return	DN20	$\frac{3}{4}$ " BSP female	Max 75°C	Weights (empty/full)		86 kg / 356kg		*Sensor	Thermowell fitted suitable for max 6.5mm temperature probe
F	Cold water inlet	DN50	2" BSP female		Weights (empty, packaged on pallet)		91 kg			
G	Hot Water outlet	DN50	2" BSP female							
H	TPR (x2)	DN25	1" BSP female							

Rinnai NZ Limited
 105 Pavilion Drive
 Mangere, Auckland
 2022

270L Commercial Tank
 (MEC0270625E)

Designed:	Spec #:
Drawn:	Date:
Scale @ A3:	Rev:
Scale @ A4:	