



Standard Connection Sizes				Specifications				Construction	
				Outer					
A	Cold Inlet	DN50	2" BSP female	Water Pressure	TPR	1000 kPa	46kW 20mm supplied	Outer Tank	Coloursteel
B	Cold Inlet	DN20	3/4" BSP female		PLV	700 kPa (approx.)	NOT SUPPLIED	Inner Tank	Enamel Steel
C	Sensor Pocket	DN20	3/4" BSP female		PRV (Cold Water)	850 kPa (approx.)	NOT SUPPLIED	Insulation	51mm of polyurethane-injected foam
D	Heat source return	DN50	2" BSP female					Anodes	2 x 25mm
E	Heat source return	DN20	3/4" BSP female	Controlled heating source supply temp.		maximum 75°C		*Sensor	Thermowell fitted suitable for max 6.5mm temperature probe
F	Hot Water Outlet	DN50	2" BSP female	Weights (empty/full)		101 kg / 431 kg			
G	TPR (x2)	DN25	1" BSP female	Weights (empty, packaged on pallet)		105 kg			

Rinnai NZ Limited
 105 Pavilion Drive
 Mangere, Auckland
 2022

330L Commercial Tank
 (MEC0330625E)

Designed:	Spec #:
Drawn:	Date:
Scale @ A3:	Rev:
Scale @ A4:	