



Standard Connection Sizes			Specifications					Construction	
			Outer		Water Pressure				
A	Cold Inlet	DN50	2" BSP female		TPR	1000 kPa	46kW 20mm supplied	Outer Tank	Coloursteel
B	Cold Inlet	DN20	3/4" BSP female		PLV	700 kPa (approx.)	NOT SUPPLIED	Inner Tank	Enamel Steel
C	Sensor Pocket	DN20	3/4" BSP female	6.5 mm i.d.	PRV (Cold Water)	850 kPa (approx.)	NOT SUPPLIED	Insulation	51mm of polyurethane-injected foam
D	Heat source return	DN50	2" BSP female	Max 75°C	Controlled heating source supply temp.			Anodes	2 x 25mm
E	Heat source return	DN20	3/4" BSP female	Max 75°C	maximum 75°C			*Sensor	
F	Hot Water Outlet	DN50	2" BSP female		Weights (empty/full)	125 kg / 565 kg	Thermowell fitted suitable for max 6.5mm		temperature probe
G	TPR (x2)	DN25	1" BSP female		Weights (empty, packaged on pallet)	140 kg			
Rinnai NZ Limited 105 Pavilion Drive Mangere, Auckland 2022			440L Commercial Tank (MEC0440720E)					Designed:	Spec #:
					Drawn:	EP	Date:		
					Scale @ A3:		Rev:		
					Scale @ A4:				