

Disclaimer: © 2015. The copyright of this document is the property of Rinnai New Zealand Ltd and shall not be reproduced, copied, loaned, Disposed of directly, or indirectly, nor used for any purpose other than that for which it is specifically furnished without prior consent. This information is intended solely as a guide for use of Rinnai products. Before using you should ensure that the product is suitable for us in the specific application. Nothing in this information constitutes a statement of fitness for particular purpose and appropriate expert advice is to always be obtained. info@rinnai.co.nz

> Issue: 1 Note:


- Example shows flue termination assembly of 1x1200mm Flue pipe; 2x600mm Flue pipes; 2x Flue elbow 45°; 2xWall straps and Roof cowl
- Can be used combination of whole range of RDV3611 flue pipes. Pipes cannot be cut in size
- Maximum flue length 5.4m
- Maximum two 45° bends allowed
- Minimum clearance from the inner flue to a combustible material must be greater than 25 mm






**Front** 

**Back View** 





Left

Right

© 2015 Rinnai New Zealand Ltd. Rinnai is constantly improving its products, and as such, all information and specifications are subject to change or variation without notice

0800 746 624

Family: fire\_rinnai\_symmetry3611\_standard

Type: symmetry3611\_standard

Scale: 1:50



Symmetry 3611 - Vertical Offset Flue Elevations